

KM302

Central de detección de monóxido de carbono para aparcamientos - 2 Zonas.

The KM302 is a 2 Zone Carbon Monoxide (CO) detection control panel designed for applications where concentrations of CO may accumulate and needs to be controlled in order to protect lives. The panel is able to accommodate 2 supervised detection zone using KMD300 CO detectors. The panel is compliant with UNE 23-301-88, CE, WEEE and RoHS.



Details

- Elegant design
- 2 Supervised CO detection zone
- Easy to install and to use
- Language customisation using language inserts
- Clear and accurate display of CO levels per zone
- Up to 15 detectors per zone
- Fast response times
- Extraction and alarm outputs per zone
- Supervision of all CO detectors and zones
- Using surface mount technology with low current consumption
- Compatible with KMD300 CO detectors
- UNE 23300:1984, CE, WEEE and RoHS compliant
- External and internal power supply support

KM302

Central de detección de monóxido de carbono para aparcamientos - 2 Zonas.

Technical specifications

Electrical

Consumo de corriente	95 W max.
Voltaje de funcionamiento	230 VAC \pm 10% 50 Hz

Zone

Cantidad de dispositivos por lazo	15 max.
Zone input voltage	10 - 20 VDC
Supply current	1 A max.
CO Sensitivity	0 - 300 ppm
Cable requirement	3 core 1.5 mm ²
Cable length	350 m max.

Physical

Dimensiones físicas	297 x 307 x 109 mm (W x H x D)
Peso neto	3 kg
Entradas de cable	4 x 20 mm (\emptyset , top)

Environmental

Temperatura de funcionamiento	0°C to +40°C
Temperatura de almacenamiento	-10°C to +70°C
Humedad relativa	10% to 95% non condensing

Relay

No. of relays per zone	3
Contact rating	5 A at 30 VDC or 8 A at 250 VAC
Switching power	150 W max.



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 23 July 2021 - 10:47