

VENF.EX15793 - FLEXIBLE SPRINKLER HOSE WITH FITTINGS

Flexible Sprinkler Hose with Fittings

See General Information for Flexible Sprinkler Hose with Fittings

AG FIRE SPRINKLER SL
C/ALFOZ DE BRICIA N 4
POL. IND. VILLALONQUEJAR
09001 BURGOS, SPAIN

EX15793

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
AG-FLEX.B-700 braided	200	150	1x1/2	2.3 (700)	2	5	33	Limited
AG-FLEX.B-1000 braided	200	150	1x1/2	3.3 (1000)	3	5	65	Limited
AG-FLEX.B-1200 braided	200	150	1x1/2	3.9 (1200)	3	5	67	Limited
AG-FLEX.B-1500 braided	200	150	1x1/2	4.9 (1500)	3	5	84	Limited
AG-FLEX.B-1800 braided	200	150	1x1/2	5.9 (1800)	3	5	101	Limited
AG-FLEX.B-700 braided	200	150	1x3/4	2.3 (700)	2	5	36	Limited
AG-FLEX.B-1000 braided	200	150	1x3/4	3.3 (1000)	3	5	59	Limited
AG-FLEX.B-1200 braided	200	150	1x3/4	3.9 (1200)	3	5	73	Limited
AG-FLEX.B-1500 braided	200	150	1x3/4	4.9 (1500)	3	5	77	Limited
AG-FLEX.B-1800 braided	200	150	1x3/4	5.9 (1800)	3	5	105	Limited
AG-FLEX.U-700 unbraided	200	150	1x1/2	2.3 (700)	2	5	33	Limited
AG-FLEX.U-1000 unbraided	200	150	1x1/2	3.3 (1000)	3	5	65	Limited

AG-FLEX.U-1200 unbraided	200	150	1x1/2	3.9 (1200)	3	5	67	Limited
AG-FLEX.U-1500 unbraided	200	150	1x1/2	4.9 (1500)	3	5	84	Limited
AG-FLEX.U-1800 unbraided	200	150	1x1/2	5.9 (1800)	3	5	101	Limited
AG-FLEX.U-700 unbraided	200	150	1x3/4	2.3 (700)	2	5	36	Limited
AG-FLEX.U-1000 unbraided	200	150	1x3/4	3.3 (1000)	3	5	59	Limited
AG-FLEX.U-1200 unbraided	200	150	1x3/4	3.9 (1200)	3	5	73	Limited
AG-FLEX.U-1500 unbraided	200	150	1x3/4	4.9 (1500)	3	5	77	Limited
AG-FLEX.U-1800 unbraided	200	150	1x3/4	5.9 (1800)	3	5	105	Limited

Model AG-FLEX.B series are intended to be installed with the L-Bracket and S-Bracket in accordance with the manufacturer's installation instructions dated June 12, 2018.

Model AG-FLEX.B and Model AG-FLEX.U series are intended to be installed with the L-Bracket and S-Bracket in accordance with the manufacturer's installation instructions dated January 14, 2019.

Trademark and/or Tradename:



Last Updated on 2019-05-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"