

FOAM CONCENTRATE

Model AG-HFE 2%

Multiexpansion fluor free concentrate

EN 1568
Part 1, 2, 3 & 4



PRODUCT DESCRIPTION

AG-HFE 2% is specially designed to be used with high and medium expansion generators. These are foam that can be used with A or B fire types.

It is a foaming agent formulated with synthetic surfactants, biodegradable, and with high resistance to water hardness, for use in conventional foam generators in which it forms a foam of good stability and slow drainage, being able to be used with both fresh water as with sea water.

AG-HFE 2% is suitable for the production of high, medium and low expansion foam, depending on the type of generator used, designed to combat fires of classes A (solids), B (liquid hydrocarbons) and LNG and LPG installations. The product has qualities far superior to conventional foams in its use in solution in seawater, being therefore very suitable for use in ships, platforms and other facilities onshore.

AG-HFE 2% in high expansion reaches ratios that range between 500 and 1000.

When used with medium expansion nozzles they can be used in outdoor fires (spills, etc.)

In low expansion, it achieves good performance when used with spray nozzles in both Class A and Class B fires, the latter in gentle application.

Its dosage is 2%, in freshwater and seawater, both in low, medium and high expansion.

The range of synthetic foams is certified according to EN-1568.

Every multiexpansion synthetic foam concentrates are highly biodegradable.

TECHNICAL DATA

Model	AG-HFE 2%
Use concentration	2%
Fire classes	A and B
Specific gravity (at 20°C)	1,06 ± 0,02 g / ml
PH (at 20°C)	7,5 – 8,0
Expansion ratio	Low expansion: 9.0 Medium expansion: >125
Viscosity (at 20°C)	20 mPa/s
25% Draining time	Low expansion: 7:00 Medium expansion: >12:00
Storage temperature	-15°C to +50°C (5°F to 122°F)
Freezing point (solidification temperature)	<-15°C (5°F)

APPLICATIONS

This foam concentrate will provide protection for a wide range of hazardous areas such as:

- Crash Fire Rescue.
- Defense Facilities.
- Storage tanks.
- Truck/Rail loading or unloading facilities.
- Processing/Storage facilities.
- Docks/Marine tankers.
- Flammable liquid containment areas.
- Liquid gas installation.

FEATURES

This foam concentrate is:

- Suitable for use with non-aspirating equipment such as fog nozzles and water spray systems.
- Suitable for use with either fresh or salt water.
- Suitable for use with deluge or closed head foam water sprinkler systems.

DISCHARGE DEVICES

This foam concentrate is suitable for use with the following discharge devices:

- Foam Chambers.
- Non air-aspirating sprinkler heads or spray nozzles.
- Standard water fog nozzles for handlines and monitors.
- Foam Makers for use with either Floating Roof Storage tanks or Dike/Bund protection systems.
- High back pressure foam makers for subsurface base injection system.

PROPORTIONING

This foam concentrate is designed for use with the following types of proportioning equipment:

- Fixed or portable in-line eductors.
- In-line balanced pressure and pump pressure proportioning skid.
- Bladder tank proportioning systems.
- Handline, air-aspirating nozzles with fixed eductor pickup tube.
- Fire pump proportioners.

STORAGE AND MAINTENANCE

AG-HFE 2% may be stored in its shipping container without change in its original physical or chemical characteristics. Shelf life is expected to be 20 years or more when stored at recommended temperatures and in original containers. It does not show significant sedimentation or precipitation in storage or after temperature cycling.

The concentrate must be stored at temperatures between -15°C and +50°C.

Synthetic foam concentrates should only be stored in stainless steel (Type 304L or 316), reinforced fiberglass polyester with a vinyl ester resin internal layer coating or plastic containers.

The physical properties and specifications of the foam concentrate should be tested after 5 years from the production date, and thereafter retested each year.

ENVIRONMENTAL IMPACT

This foam concentrate is biodegradable.

TOXICITY

This foam concentrate is low in toxicity to humans or animals and can be treated in sewage treatment plants.

ORDERING INFORMATION

Specify:

Model	
Concentration	
Homologations	
Quantity	AG-HFE 2% – JA 20 L Jerry can AG-HFE 2% – JB 25 L Jerry can AG-HFE 2% – D 200 L Drum AG-HFE 2% – IBC 1000 L IBC

AG FIRE SPRINKLER

AG Fire Sprinkler offers a wide selection of components. Then a list of products is presented by AG Fire Sprinkler, we can offer all these components, made with precision to protect people, anywhere, anytime.

- Sprinklers
 - Basic
 - Extended Coverage
 - Storage
 - Dry
 - Accessories
- System Valves
 - Wet
 - Dry
 - Preaction Equipment
 - Accessories
- Spray System Open Nozzles
 - High Velocity Nozzles
 - Medium Velocity Nozzles
 - Window Nozzles
 - Hydrosshield Nozzles
 - Mushroom Type Nozzles
- Foam equipment
 - Bladder Tanks
 - Proportioners for Bladder Tanks
 - Foam Discharge Equipment
 - Foam Concentrates
- Alarm Check Valves for Water Spray and Foam
 - Clapper Deluge Valves
 - Diaphragm Deluge Valves
- Monitors
 - Manual Monitors
 - Remote Monitors
 - Monitor Towers
 - Monitors Trolleys
- Valves
 - Butterfly Valves
 - Gate Valves
 - Check Valves
 - Pressure Control Valves
 - Test and Drain
 - Hose, Hydrant and Fire Connection Valves
 - Fire Department Connections

The equipment presented in this bulletin is to be installed in accordance with the latest published Standard of the National Fire Protection Association, Factory Mutual Research Corporation, or other similar organizations and also with the provisions of governmental codes or ordinances whenever applicable. This documentation is not contractual. AG Fire Sprinkler reserves the right to any kind of change without notice.
