



## HMRZ.EX15963 Gate Valves

[Page Bottom](#)

### Gate Valves

[See General Information for Gate Valves](#)

#### AG FIRE SPRINKLER SL

EX15963

C/ALFOZ DE BRICIA N 4

POL. IND. VILLALONQUEJAR

09001 BURGOS, SPAIN

Pattern	Model	Size, in.	End Configuration	Rated Pressure, psig
NRS	NRS200	2-1/2, 3, 4, 6, 8, 10, 12	Flanged and Mechanical	200
NRS	NRS250	2-1/2, 3, 4, 6, 8, 10, 12	Flanged and Mechanical	250
OS&Y	OSY200	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	200
OS&Y	OSY200	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	250
OS&Y	OSY175T	3/4, 1, 1-1/4, 1-1/2, 2	Threaded	175
NRS	NRS175-1	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	175
	NRS200-1			200
	NRS250-1			250
	NRS300			300
OS&Y	OSY175-1	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	175
	OSY200-1			200
	OSY250-1			250
	OSY300			300
OS&Y	VCOSY300	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F	300
OS&Y	VCOSY300-16	2, 2.5, 3, 4, 5, 6, 8	F by F (BS Flange)	300
OS&Y	VCOSY250-16	10, 12	F by F (BS Flange)	250
NRS	VCNRS300IP	2.5, 3, 4, 5, 6, 8	F by F (BS Flange)	300
NRS	VCNRS250IP	10, 12	F by F (BS Flange)	250
NRS	VCNRS300V	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
NRS	VCNRS250V-16	10, 12	F by F (BS Flange)	250
NRS	VCNRS300V-16	2.5, 3, 4, 5, 6, 8	F by F (BS Flange)	300
NRS	VCNRS300T	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
NRS	VCNRS300T-16	2.5, 3, 4, 5, 6, 8	F by F (BS Flange)	300
NRS	VCNRS250T-16	10, 12	F by F (BS Flange)	250
NRS	VCNRS300P	4, 5, 6, 8, 10, 12	F by F (ANSI Flange)	300
NRS	VCNRS300P-16	4, 5, 6, 8	F by F (BS Flange)	300
NRS	VCNRS250T-16	10, 12	F by F (BS Flange)	250
OS&Y	VCOSY300G	2, 2.5, 3, 4, 5, 6, 8, 10, 12	G by G	300
NRS	VCNRS300GV	2.5, 3, 4, 5, 6, 8, 10, 12	G by G	300
NRS	VCNRS250GV-16	10, 12	G by G	250
NRS	VCNRS300GV-16	2.5, 3, 4, 5, 6, 8	G by G	300

NRS	VCNRS300GP	4, 6, 8, 10, 12	G by G	300
OS&Y	VCOSY300FG	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	300
OS&Y	VCOSY250FG-16	10, 12	F by G (BS Flange)	250
OS&Y	VCOSY300FG-16	2, 2.5, 3, 4, 5, 6, 8	F by G (BS Flange)	300
NRS	VCNRS300FG	2.5, 3, 4, 5, 6, 8, 10, 12	F by G (ANSI Flange)	300
NRS	VCNRS250FG-16	10, 12	F by G (BS Flange)	250
NRS	VCNRS300FG-16	2.5, 3, 4, 5, 6, 8	F by G (BS Flange)	300
NRS	VCNRS300MV	3, 4, 6, 8, 10, 12	MJ by MJ	300
NRS	VCNRS300MT	3, 4, 6, 8, 10, 12	MJ by MJ	300
NRS	VCNRS300MP	4, 6, 8, 10, 12	MJ by MJ	300
OS&Y	VCOSY300M	2, 2.5, 3, 4, 6, 8, 10, 12	MJ by MJ	300
OS&Y	VCOSY232	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F (DIN Flange)	232
NRS	VCNRS232IP	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (DIN Flange)	232
NRS	VCNRS232V	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (DIN Flange)	232
NRS	VCNRS232T	2.5, 3, 4, 5, 6, 8, 10, 12	F by F (DIN Flange)	232
NRS	VCNRS232P	4, 5, 6, 8, 10, 12	F by F (DIN Flange)	233

Last Updated on 2016-05-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".